

# Ink & Stain Resistant — Ultrafabrics

We have all experienced the dreaded results of a bad spill. Our **Ink & Stain** solution helps alleviate cleaning stress by uniting repellency without sacrificing style. It is trusted across all markets, perfect for any environment you want to defend against pesky stains. From busy commercial environments to homes with pets and kids, our Ink & Stain resistance is universal in its utility.



---

## Featured Collections —

Reef Pro | Ultraleather Pro | Ultraleather Pro IFR\*

- Superior durability – industry-leading 14+ weeks hydrolysis results
- Premium, 100% polycarbonate construction withstands harsh cleaners and disinfectants
- Bleach cleanable with 1:5 bleach/water solution
- Enhanced resistance to tough stains including ballpoint pen, betadine, blood, denim dye, mustard & ketchup, and red wine
- Select styles include antimicrobial protection
- SCS Indoor Advantage Gold Certified and REACH compliant

**Not that you would, but you could.**

\*Only available in the UK.



Antimicrobial\*



Ink & Stain Resistant

# Ink & Stain Resistant

## Application

Interior Upholstery

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
100% Reinforced Rayon Backing  
containing TENCEL™ Modal fibers (Ultraleather Pro)  
65% Polyester, 35% Rayon Backing (Reef Pro)  
50% Modacrylic, 50% Rayon Backing (Ultraleather Pro IFR)

### Weight:

Approx. 9.7 - 12.1 oz. Per Square Yard  
Approx. 330 - 410 Grams Per Square Metre

### Thickness:

Approx. 0.80 - 1.15 Millimetres

### Width:

54 Inches / 137 Centimetres

### Repeat:

None

## Performance

### Abrasion:

ASTM D4157 / 400,000 - 500,000 Double Rubs (Wyzenbeek)\*  
BS EN ISO 12947-2 / 120,000 - 200,000 Rubs (Martindale)\*  
\*meets or exceeds

### Hydrolysis:

14+ Weeks  
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Tensile Strength: BS EN ISO 1421

Antimicrobial: ASTM E2180\*

## Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4  
ISO 105 B02, Grade 6

Crocking: AATCC 8, Grade 4-5 Wet & Dry

## Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- IMO FTPC Part 8
- BS EN 1021 Parts 1 & 2\*\*
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)

## Included Collections Resist:

- Ballpoint ink
- Blood
- Mustard and Ketchup
- Betadine
- Denim\*
- Red Wine

\* Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

\*Only pertains to Ultraleather Pro & Ultraleather Pro IFR

\*\*Only pertains to Ultraleather Pro & Ultraleather Pro IFR



INDOOR ADVANTAGE GOLD FURNITURE

TENCEL™ is a trademark of Lenzing AG

[ultrafabricsinc.com](http://ultrafabricsinc.com)

Ultrafabrics® and logo and Ultraleather® are registered trademarks of Ultrafabrics Inc. Made in Japan.

2/22

